




# Planar QE7550

4K LCD Display

The Planar® QE7550 is a large format 4K (3840 x 2160) LCD display that is ideal for applications ranging from dynamic digital signage to collaborative meeting spaces. It supports native 4K resolution at up to 60Hz via HDMI 2.0 and DisplayPort 1.2, enabling smooth motion video and mouse tracking. Users can view four sources simultaneously in quad layout and receive remote monitoring alerts via email when a designated event occurs. For precise image control, adjustments can be made within each of the four zones allowing users to optimize the picture quality at the source level. Operating without fans, it provides whisper quiet operation and reduced points of failure.



SPECIFICATION	DETAIL
Product Name	Planar QE7550
Planar Part Number	997-8795-01
Display Resolution	Ultra HD (3840 x 2160)
Screen Size	75 in. (diagonal)
Aspect Ratio	16:9
Display Active Area	65.0" (1650mm) x 36.5" (928mm)
Cabinet Dimensions (W x H x D)	66.1" x 37.8" x 3.2" (1680mm x 959mm x 82mm)
Bezel Width	0.60" (15.3mm) left/right; 0.61" (15.4mm) top/bottom
Brightness (typ)	500 nits
Response Time (typ)	6 ms
Frame Rate	120Hz
Contrast Ratio (typ)	1200:1
Contrast Ratio - Dynamic	20,000:1
Viewing Angle (typ)	178°
Color Gamut	72% NTSC
Display Color	>1 billion colors. Full 10 bit data path
Modes	3840x2160 @ 24/25/30/60Hz; 1920x1080 @ 24/25/30/50/60Hz; 480p, 576p, 720p @ 50/60 Hz; 1080p @ 24/25/30/50/60Hz; 1080i @ 50/60 Hz
Pixel Pitch	0.429 mm
Weight	115 lbs (52 kg)
Backlight	LED

<b>Line Voltage</b>	100-240V; 50/60Hz
<b>Power Consumption (typ)</b>	195W (standby: <1W)
<b>Operating Temperature</b>	0° to +35°C (32° to 95°F) at up to 1500m, 0° to +30°C (32° to 86°F) at up to 3000m
<b>Humidity</b>	20 - 85% RH (non-condensing)
<b>Approvals</b>	FCC Class A, cTUVus, RoHS
<b>External Connections</b>	DisplayPort 1.2 x 1, HDMI 2.0 x 2 (HDCP 2.2), HDMI 1.4 x 2
<b>Audio Output</b>	PC Line Out, S/PDIF
<b>Multi-Source Views</b>	Quad only
<b>Display Control</b>	IR, RS-232, LAN, Keypad
<b>Speakers</b>	10W x 2 built-in
<b>Orientation</b>	Landscape/Portrait
<b>Mounting</b>	VESA: 600 x 400 mm
<b>Fanless</b>	Yes
<b>HD format</b>	4K UHD 2160p
<b>Display Technology</b>	Edge-lit LED LCD
<b>Haze</b>	3%
<b>Surface Treatment</b>	AG
<b>Recommended Usage</b>	Up to 24x7 operation
<b>Warranty</b>	3 years Advance Exchange
<b>Options / Features</b>	TAA compliant
<b>In the Box</b>	QE7550 display, power cord, IR sensor, remote control, and USB drive containing User Manual and USB-to-serial driver
<b>UPC</b>	8 10689 00737 1

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 10/6/2021*

*© Copyright 2021 Planar Systems, Inc. All rights reserved*

Planar utilizes HDMI® standards in this product.

The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.