



# PXN2400

## 24" LCD Monitor

The Planar® PXN2400 24" full HD IPS LED LCD monitor that features a frameless bezel, thin profile, modern design, wide viewing angles, numerous inputs and integrated TrueMedia™ speakers. The Planar PXN2400 is a great fit in either home or office applications.



| SPECIFICATION          | DETAIL                                                   |
|------------------------|----------------------------------------------------------|
| Product Name           | PXN2400                                                  |
| Planar Part Number     | 998-2121-00                                              |
| Viewable Size          | 23.8" diagonal (20.75" horizontal x 11.67" vertical)     |
| Aspect Ratio           | 16:9                                                     |
| Contrast Ratio (typ)   | 1000:1                                                   |
| Viewing Angle (typ)    | 178° Horizontal and 178° Vertical (Specified at CR>10:1) |
| Response Time (typ)    | 5 ms (GTG)                                               |
| Brightness (Typical)   | 250 cd/m <sup>2</sup>                                    |
| Display Type           | IPS LCD Active Matrix Flat Panel Display (TFT)           |
| Display Resolution     | 1920 x 1080, full HD                                     |
| Tilt Range             | -5° to +20°                                              |
| Palette                | 16.7 million colors                                      |
| Pixel Pitch            | 0.2745 mm                                                |
| Refresh Rate           | 55~76 Hz (60 Hz recommended)                             |
| Dimensions (W x H x D) | 21.24" x 15.5" x 8.26" (539.5 mm x 393.5 mm x 209.9 mm)  |

|                                 |                                                                                                                                                                                     |
|---------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>Dimensions without Stand</b> | 21.24" x 12.80" x 1.53" (539.5 mm x 325.3 mm x 38.8 mm)                                                                                                                             |
| <b>Panel Depth</b>              | 1.53" (38.8 mm)                                                                                                                                                                     |
| <b>Display Weight</b>           | 8.6 lb (3.9 kg); Weight without stand: 7.5 lb (3.4 kg)                                                                                                                              |
| <b>Shipping weight</b>          | 10.8 lb (4.9 kg)                                                                                                                                                                    |
| <b>Video Inputs</b>             | HDMI®, DisplayPort, VGA                                                                                                                                                             |
| <b>HDCP</b>                     | Yes                                                                                                                                                                                 |
| <b>Audio Output</b>             | 2W x 2, headphone out                                                                                                                                                               |
| <b>External Connections</b>     | HDMI 19-pin, DisplayPort 20-pin, VGA 15-pin, 3.5 mm audio in, 3.5mm headphone out                                                                                                   |
| <b>Compatibility</b>            | PC and Mac® (adapter may be required for Mac)                                                                                                                                       |
| <b>Power Supply</b>             | Internal                                                                                                                                                                            |
| <b>Power Consumption (max)</b>  | 25 Watt Typical (<0.5 Watt standby)                                                                                                                                                 |
| <b>Power Requirements</b>       | AC 100/240 VAC                                                                                                                                                                      |
| <b>Operating Temperature</b>    | 0° to +40°C (32° to 104°F)                                                                                                                                                          |
| <b>Humidity</b>                 | 10 - 90% RH (non-condensing)                                                                                                                                                        |
| <b>Mount</b>                    | Built-in 100 mm VESA, back                                                                                                                                                          |
| <b>Product Approvals</b>        | FCC-B, CE, UL/cUL, RoHS                                                                                                                                                             |
| <b>Recommended Usage</b>        | Up to 16 hours per day                                                                                                                                                              |
| <b>Service and Support</b>      | 3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US.      |
| <b>Options / Features</b>       | IPS Wide color consistent viewing angle, Nearly Borderless bezel, Discreet branding, Anti-glare coating, Multi-language display, On screen display (OSD), Kensington® Security Slot |
| <b>Blue Light Reduction</b>     | Yes                                                                                                                                                                                 |
| <b>Flicker Free</b>             | Yes                                                                                                                                                                                 |
| <b>In the Box</b>               | PXN2400 23.8" LED LCD Monitor, Power Cord, VGA Cable, HDMI Cable, Audio Cable, User's Guide                                                                                         |
| <b>UPC</b>                      | 8 10689 00800 2                                                                                                                                                                     |

**HDMI®**

Planar utilizes HDMI® standards in this product. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

For more information, please visit [www.planar.com](http://www.planar.com)

*Specifications are subject to change without notice.*

*Specification Report Date: 5/21/2024*

*© Copyright 2024 Planar Systems, Inc. All rights reserved*