



Clarity Matrix G3 MX55X3

LCD Video Wall System

The Clarity® Matrix® G3 MX55X3 is a 55" LCD video wall display with a narrow tiled bezel width of 2.6mm that provides a nearly seamless digital canvas, outstanding tiled visual performance, extended operation and requires minimal installation space. Designed for 24x7 operation, the Clarity Matrix G3 MX55X3 features 700 nits brightness, commercial-grade IPS LCD panel, LED backlight technology and Full HD resolution—making it the ideal video wall for high-impact, mission-critical applications.



Note: Cat6A STP (shield twisted pair) cables and connectors are required.

| SPECIFICATION | DETAIL |
|--|--|
| Technology | Commercial-grade LCD |
| Per Panel Dimensions (Including Mount) | 47.7 x 26.9 x 3.6in 1212.2 x 683.0 x 90.9mm |
| Diagonal | 55in 1396mm |
| Native Resolution Panels | 1920 x 1080 |
| Aspect Ratio | 16:9 |
| Tiled Bezel Width | 0.10in 2.6mm |
| Thermal Expansion Gap Required | 0.4 mm .02 in |
| Power Consumption (max/display) | 182W |
| Power supply voltage | 100-230V AC ± 10%, 50 to 60 Hz |
| Power Status | Diagnostics LEDs, health monitoring and alerts |
| Per Panel Weight (Including | 50.6lb 23.2kg (Landscape) 53.5lb 24.1kg (Portrait) |

| | |
|---------------------------------|---|
| Mount) | |
| Shipping weight | 106lbs 48.1kg (single pack) / 157lbs 71.3kg (dual pack) |
| Mounted Depth | 3.6in 91.44mm (wall to front of display) |
| Brightness (typ) | 700 cd/m ² or nits |
| Contrast ratio (full field) | 1000:1 |
| Contrast Ratio - Dynamic | 140000:1 (typ) |
| Response Time (typ) | 8 ms |
| Full viewing angle | 178° |
| Haze | 28% |
| Video Inputs (Controller) | 4x HDMI® 2.0 (w/ HDCP 2.2), 1x DisplayPort 1.2 (VC4H-BP+, VC9H-BP+ only) |
| Video Outputs (Controller) | VC9H-BP+: 9x RJ45 8P8C, 1x DisplayPort 1.2 VC4H-BP+: 4x RJ45 8P8C, 1x DisplayPort 1.2 VC4-HSL: 4x RJ45 8P8C |
| High Speed Link (HSL) | VC4-HSL: 2 Out, 2 In, QSFP+ cable |
| HSL Loop Capacity | VC4-HSL: 80Gb. 4x 4K or 16x Full HD video sources |
| Video Extension built-in | 200ft 60m over STP CAT6 |
| Control | IR Remote Control, RS-232, USB, Network, Planar WallDirector Software |
| Sync | Mini BNC In/Out |
| Backlight control | Individual and wall control |
| Backlight sensing and reporting | At display level |
| Display module position sensing | Auto-sensing integrated |
| Backlight life (1/2 brightness) | 50,000 Hrs |
| Power Supply | Offboard Redundant Optional Hot Swap |
| Wall Mount | Planar® EasyAxis™ Mounting System VESA Mount (optional) |
| Acoustic Noise | LCD: <30dBA (fanless), VC: 45dBA, RPS: <40dBA @ 25°C (77°F) |
| Heat Load (max/display) | 768 BTU/hr |

| | |
|--|--|
| Operating Temperature/Humidity (degrees F/C, relative humidity) | 5° to 40° C / 20-90% RH 41° to 104° F / 20-90% RH |
| Orientation | Landscape or Portrait |
| Safety regulations | Complies with EN62368-1, FCC Class A, CISPR22/85, CE, EU RoHS |
| Cat6 Cables and Connectors | Cat6a STP (shield twisted pair) cables and connectors are required. |
| Touch Technology | Clarity Matrix MultiTouch (optional) |
| Protection | Planar® ERO-LCD™ (Extended Ruggedness and Optics™) Technology (optional) |
| Fiber Video Extension Module Option | 1 RU rack mount module drives up to 4 displays |
| Fiber Video Extension Module Outputs | 10G Duplex LC SFP+ single mode transceivers supporting distances up to 10km (32.8kft) (Single mode transceivers supporting 2km (6500ft) included) from video wall. Compatible with multi mode transceivers supporting up to 300m (980ft) from the wall. (multi mode transceivers not provided) |
| HDMI® | Planar utilizes HDMI® standards in this product. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. |

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 5/12/2024

© Copyright 2024 Planar Systems, Inc. All rights reserved