

PXV2410

24" Full HD video conferencing monitor

The slim Planar® PXV2410 is a 24" Full HD video conferencing monitor that features a built in 2MP webcam, microphone and speakers that support Windows Hello. A shutter slider ensures privacy and prevents accidental appearances on camera. An ergonomically-designed stand with height adjustment, pivot, swivel and tilt provides end user comfort while the built-in USB hub allows home, office or healthcare users to conveniently connect devices. As an added feature, one of the USB 3.0 ports provides BC1.2 and can power devices up to 1.5A.



SPECIFICATION	DETAIL
Product Name	PXV2410
Planar Part Number	998-2946-00
Viewable Size	23.8" diagonal (20.75" horizontal x 11.67" vertical)
Aspect Ratio	16:9
Contrast Ratio (typ)	1000:1
Viewing Angle (typ)	178° Horizontal and Vertical
Response Time (typ)	6 ms (GTG)
Brightness (Typical)	250 cd/m ²
Display Type	IPS LCD Active Matrix Flat Panel Display (TFT)
Display Resolution	Full HD 1080P, 1920 x 1080
Tilt Range	-5° to +20°
Palette	16.7 million colors

Pixel Pitch	0.2745 mm
Refresh Rate	48 to 76Hz (60 Hz recommended)
Dimensions (W x H x D)	24.2" x 20.5" x 9.1" (612.84 mm x 519.39 mm x 229.63 mm)
Dimensions without Stand	24.2" x 14.5" x 2.1" (612.84 mm x 367.46 mm x 52.3 mm)
Panel Depth	2.1" (52.3 mm)
Display Weight	10.8 lb/4.9kg (7.0 lb/ 3.145 kg without stand)
Shipping weight	13.3 lb (6.8 kg)
Video Inputs	HDMI®, DisplayPort, VGA
HDCP	Yes
Webcam	2.0 MP FHD camera with microphone and LED indicator (for Windows 10 Hello)
Audio Output	Integrated 2W/channel stereo speakers, headphone jack
External Connections	HDMI 19-pin, DisplayPort 20-pin, VGA 15-pin, 3.5 mm audio in, 3.5mm headphone out, USB 3.2 Gen 1 (Type B) in, USB 3.2 Gen 1 (Type A) out, USB3.2 Gen 1 (Type A) w/ BC1.2 out.
Compatibility	PC and Mac® (adapter may be required for Mac)
Power Supply	Internal
Power Consumption (max)	14.7W Typical (<0.5W standby)
Power Requirements	AC 100/240 VAC
Operating Temperature	0° to +40°C (32° to 104°F)
Humidity	10 - 85% RH (non-condensing)
Mount	Built-in 100 mm VESA, back
Product Approvals	cTUVus, CE , FCC-B, RoHS
Recommended Usage	Up to 16 hours per day
Service and Support	3-Year Customer First™ Warranty featuring FREE Advance Replacement (US only). Please see the warranty document for more details and for replacement procedures outside the US.
Options / Features	IPS panel, Wide color consistent viewing angle, Discreet branding, Height adjustment: 4.3" (120cmm), Swivel range 60° (30° left, 30° right), Pivot

	± 90°, Anti-glare coating ,Multi-language display, On screen display (OSD), Kensington® Security Slot
Blue Light Reduction	Yes
Flicker Free	Yes
In the Box	PXV2410 24" LED LCD Monitor, Power Cord, HDMI Cable, DisplayPort Cable, USB Cable, User's Guide
UPC	8 10689 00987 0
HDMI®	Planar utilizes HDMI® standards in this product. The terms HDMI, HDMI High-Definition Multimedia Interface, HDMI Trade dress and the HDMI Logos are trademarks or registered trademarks of HDMI Licensing Administrator, Inc.

For more information, please visit www.planar.com

Specifications are subject to change without notice.

Specification Report Date: 5/20/2024

© Copyright 2024 Planar Systems, Inc. All rights reserved